

HYDROTAP G5 BC40 CLASSIC CHROME





BOILING

CHILLED

FILTERED

Order Code H51703Z00AU

Zip HydroTap Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.





_			
Тар	Zip HydroTap CLASSIC Tap (Chrome)		
Water Pressure	Min 170kPa - Max 700kPa		
Water Connection	1/2" BSP (G1/2)		
Water Supply Requirements	Cold		
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve		
Power Rating	1.97kW 220-240V 50Hz		
Power Supply	1 x 10 Amp socket outlet		
Dimensions	W395mm x D464mm x H333mm		
Product Approvals	WaterMark, RCM, ARC		

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

